

Contenido Handbuch (V4.6.x)

System-/Mandanten-/Gruppen- und benutzerdefinierte Einstellungen (docs/techref)

Ab der Contenido Version 4.6.x ist die Verwendung benutzerdefinierter Einstellungen wesentlich erweitert worden.

Einige Einträge werden automatisch angelegt, mit anderen Einstellungen kann das System angepasst werden. Zur Dokumentation siehe

...\docs\techref\backend\backend.customizing.html.

Generell **addieren** sich die einzelnen Einstellungen. Z.B. kann eine einer Gruppe zugewiesene Einstellung keinem Benutzer genommen werden. Ansonsten haben Nutzereinstellungen immer Vorrang vor Gruppeneinstellungen. Ist ein Nutzer Mitglied in mehreren Gruppen, ist das Ergebnis unvorhersehbar - stellen Sie sicher, dass sich die einzelnen Gruppeneinstellungen nicht widersprechen.

Systemeinstellungen erfolgen unter Administration -> System -> Systemeinstellungen, Mandanteneinstellungen unter Administration -> Mandanten -> Mandanteneinstellungen, Gruppeneinstellungen unter Administration -> Gruppen und Nutzereinstellungen unter Administration -> Benutzer.

Angegebene Contenido-Version beachten!!!

Verfügbare Einstellungen (V4.6.18):

Common parameters

Area/Type	Property	Value (Description)	Applies to
backend	currentlogintime	Date and Time when this session has been started (automatically set by the backend)	Users
backend	lastlogintime	Date and Time when the last session was started (automatically set by the backend)	Users
backend	preferred_idclient	ID of the client which should be selected after backend login	System, Clients, Groups, Users
backend	leftframewidth	Defines the width of the left frame. Standard value is 250.	System, Clients, Group, Use

Contenido Handbuch (V4.6.x)

backend	small-navigation	(true, false): If true, a small navigation is shown. Default: false	System, Clients, Groups, Users
articles	show-new-window-checkbox	(true, false): If true, show "new window" checkbox for redirects in article properties. Note: If a redirect has been specified, the page is redirected to the new URL using an html page header. As header redirects can't open new windows, this setting is only useful, if a navigation module is used, which mentions the "open in new window" setting and adds a 'target="_blank"' to the link, if necessary. Default: false	System, Clients, Groups, Users
cms_img	directory-height	Height of the directory lister in rows, default 5	System, Groups, Users
cms_img	directory-width	Width of the directory lister in pixels, default 300	System, Groups, Users
cms_img	file-height	Height of the file lister in rows, default 5	System, Groups, Users
cms_img	file-width	Width of the file lister in pixels, default 300	System, Groups, Users
cms_img	description-height	Height of the description box in rows, default 5	System, Groups, Users
cms_img	description-width	Width of the description box in characters, default	System, Groups, Users

Contenido Handbuch (V4.6.x)

		70	
cms_img	preview-height	Height of the preview area in pixels, default 400	System, Groups, Users
cms_img	preview-width	Width of the preview window in pixels, default 600	System, Groups, Users
imagemagick	available	Set "1" if ImageMagick is available on your server to receive best results when resizing images	System, Groups, Users
modules	java-edit	Enable the java module editor	System, Groups, Users
modules	edit-with-tabs	(true, false) If set to "true" you can use the key to insert tabs in the input and output code areas (IE 6/7, FF 1.5/2). Default: false	System, Clients, Groups, Users
modules	disable-history	(true, false) If true, don't use the module history. Default: false	System, Clients, Groups, Users
modules	storeasfiles	Defines if Contenido should store modules as text files. THIS IS HIGHLY EXPERIMENTAL, ONLY USE IF YOU KNOW WHAT YOU ARE DOING! Default off.	System
modules	loadfromfiles	Defines if Contenido should load modules as text files. THIS IS HIGHLY EXPERIMENTAL, ONLY USE IF YOU KNOW WHAT YOU ARE DOING! Default	System

Contenido Handbuch (V4.6.x)

		off.	
modules	force-menu-check	If system/modulecheck is enabled, force module check while module list will be generated (instead of using database information). Default <code>\"false\"</code> ;	System, Clients, Groups, Users
system	modulecheck	if set to "false" (as string), modules aren't tested for syntax errors (needed for older PHP versions)	System
system	languageorder	If set to "name", languages in the drop-down (top right) will be shown ordered by name, if not specified or set to something else, languages will be ordered by language id (default)	System, Clients, Groups, Users
system	multiassign	If false, don't allow multi assignments for articles.	System, Clients
layout	htmlvalidator	(true, false): If true, use the HTML validator. Default: true	System, Groups, Users
newsletter	option-cronjob-available	(true, false): If true, then a newsletter option can be activated to send the newsletter using cron jobs. Note, that this option should only be used, if a real cron service is available (do not use the Contenido	System, Clients, Users

Contenido Handbuch (V4.6.x)

		<p>built-in pseudo cron service). Additionally, note, that there is a send job file available in the contenido/cronjobs folder, but it hasn't been added to the cron job list - just generate a real cron job on your server running this file. Default: false</p>	
newsletter	disable-rn-replacement	<p>(true, false): If true, "\r\n" will not be replaced by just "\n" to prevent double lines in mails. This may be a good idea on Windows-Servers. Usually, use the default setting. Default: false</p>	System
newsletter	remove_base_tag	<p>(true, false): Usually every article contains a "e;base href"e; tag. This is nice, as all links, URLs and sources can be relative and we can move the client around, as we like.</p> <p>But there is a problem with anchors: They only work, if the link to the anchor (on the same page) contains the URL of the current article (e.g. "front_content.php?idart=77#My Anchor"). This works fine, if you</p>	Client

Contenido Handbuch (V4.6.x)

		<p>are on the website, but not, if you use anchors in html newsletter articles (as the mail doesn't has this URL).</p> <p>If you like to use anchors in html newsletters, set this setting to "true" and check everything twice, as also all URLs and source path will be changed by Contenido code. Default: false</p>	
newsletter	html_username html_password	<p>If the frontend (the website) is protected using .htaccess (username/password), you have to specify html_username and html_password to be able to send html newsletters (as html newsletters are just usual articles). Default: empty or not specified</p>	Client
frontendusers	pluginsearch	<p>(true, false): If true, the frontend users menu also searches trough plugins. However, searching trough plugins have a huge performance impact on the list. If you have alot of frontend users, set this to false to disable this function. Default: true</p>	System, Clients, Users

Contenido Handbuch (V4.6.x)

frontendusers	pluginsearch_valid_plugins	If pluginsearch is set to true, you can hereby limit the plugins to search over. This property must be a comma-separated list (no whitespaces) of all plugins that should be used for pluginsearch. All other plugins will be skipped to improve performance.	System, Clients, Users
generator	xhtml	(true, false): Defines if the tags generated by Contenido should be XHTML compliant. WARNING: This does not alter the HTML code in your layouts and modules! You have to revise your modules and layouts to be XHTML compliant. Default: false.	System, Clients
generator	basehref	(true, false): Defines if Contenido should automatically insert a base href tag. Default: true.	System, Clients

SPAW related parameters

wysiwyg	spaw-styles	The CSS style names which appear in the styles drop-down.	System, Groups, Users
wysiwyg	spaw-stylesheet-file	The stylesheet file to use for the WYSIWYG.	System, Groups, Users

Contenido Handbuch (V4.6.x)

wysiwyg	spaw-toolbar-mode	The toolbar mode to use. Allowed values: default, full, mini, nofont, sidetable	System, Groups, Users
wysiwyg	spaw-height	The height of the SPAW editor widget (fallback mode, currently not used)	System, Groups, Users
wysiwyg	spaw-height-html	The height of the SPAW editor when editing CMS_HTML elements	System, Groups, Users
wysiwyg	spaw-height-head	The height of the SPAW editor when editing CMS_HEAD elements	System, Groups, Users
wysiwyg	spaw-width	The width of the SPAW editor widget (fallback mode, currently not used) (usage: XX% => percentage statement / XX => pixel statement)	System, Groups, Users
wysiwyg	spaw-theme	SPAW editor theme, defaults to "contenido"	System, Groups, Users

tinyMCE related parameters

Starting with Contenido V4.6.16 all tinyMCE settings which may be specified for tinyMCE and the plugins may be specified as system, client, group or user setting. Use "tinymce" as type and as name the name of the parameter according to the tinyMCE documentation.

These parameters can't be set using a setting: document_base_url, file_browser_callback

tinymce	content_css	Defines the stylesheet to include within tinyMCE (<= V4.6.15: wysiwyg/tinymce-stylesheet-file).	System, Groups, Users
tinymce	theme_advanced_st	Defines the	System, Groups,

Contenido Handbuch (V4.6.x)

	yles	available styles in the tinyMCE style dropdown (<= V4.6.15: wysiwyg/tinymce-styles)	Users
tinymce	width	Defines the width of tinyMCE (<= V4.6.15: wysiwyg/tinymce-width, default 100%)	System, Groups, Users
tinymce	height	Defines the height if tinyMCE (<= V4.6.15: wysiwyg/tinymce-height, default 480px)	System, Groups, Users
tinymce	contenido_height_html	Overrides the tinyMCE height when editing the CMS_HTML element (<= V4.6.15: wysiwyg/tinymce-height-html)	System, Groups, Users
tinymce	contenido_height_head	Overrides the tinyMCE height when editing the CMS_HTMLHEAD element (<= V4.6.15: wysiwyg/tinymce-height-head)	System, Groups, Users
tinymce	contenido_gzip	If set to "true" use gzip compression. The server has to provide the compression method. Default: "false"	System, Groups, Users
tinymce	contenido_toolbar_mode	Defines the tinyMCE toolbar mode (default "full"). Available choices: full, simple, mini, custom (<= V4.6.15: wysiwyg/tinymce-toolbar-mode)	System, Groups, Users

Contenido Handbuch (V4.6.x)

tinymce	theme_advanced_buttons1 theme_advanced_buttons2 theme_advanced_buttons3	Defines which items should be shown on the first/second/third toolbar. Please have a look at the tinyMCE documentation to find out which items you can use (<= V4.6.15: wysiwyg/tinymce-toolbar1/2/3). Only used if the toolbar mode is "custom".	System, Groups, Users
tinymce	plugins	Defines which plugins should be loaded (<= V4.6.15: wysiwyg/tinymce-plugins). Only used if the toolbar mode is "custom".	System, Groups, Users
tinymce	valid_elements	Defines which elements are allowed. See tinyMCE documentation for more information (<= V4.6.15: wysiwyg/tinymce-valid-elements). Default: +a[name href target title],strong/b[class],em/i[class],strike[class],u[class], p[dir class align],ol,ul,li,br,img[class src border=0 alt title hspace vspace width height align],sub,sup,blockquote[dir style],table[border=0 cellspacing cellpadding width height class align],tr[class rowspan width height align valig	System, Groups, Users

Contenido Handbuch (V4.6.x)

		n],td[dir class colspan rowspan width height align valign],div[dir class align],span[class align],pre[class align],address[class align],h1[dir class align],h2[dir class align],h3[dir class align],h4[dir class align],h5[dir class align],h6[dir class align],hr	
tinymce	extended_valid_elements	Defined which elements are allowed. These elements are added to valid_elements (<= V4.6.15: wysiwyg/tinymce-extended-valid-elements). Default: form[name action method],textarea[name style cols rows],input[type name value style onclick],a[name href target title onclick],img[class src border=0 alt title hspace vspace width height align onmouseover onmouseout name],hr[class width size noshade],font[face size color style],span[class align style]	System, Groups, Users
tinymce	contenido_background_color	Defines the tinyMCE background color (any valid CSS color value can be used). If you use an HTML hex color code, also include the # sign before the color (e.g. #ffffff).	System, Groups, Users

Contenido Handbuch (V4.6.x)

		Default is "white" (<= V4.6.15: wysiwyg/tinymce-backgroundcolor).	
tinymce	convert_urls	(true, false): Defines, if URLs will be converted (e.g. to relative URLs) at all. Please note, that URLs should be converted (e.g. for the time you may have to change the domain or server path). Default: true (<= V4.6.15: wysiwyg/tinymce-convert-urls)	System, Clients, Groups, Users
tinymce	relative_urls	(true, false): If convert_urls is true, then this setting specifies, if URLs will be converted to relative or absolute URLs. Please note, that relative URLs should be used (e.g. for the time you may have to change the domain or server path). Default: true (<= V4.6.15: wysiwyg/tinymce-relative-urls)	System, Clients, Groups, Users
tinymce	contenido_lists	If specified, adds dropdown lists with links for all articles (Insert Link popup window), images (Insert Image popup window) and/or all media/flash files (Insert Media/Flash popup window). Valid values are: link, image, media,	System, Groups, Users

Contenido Handbuch (V4.6.x)

		<p>flash. Values have to be separated by a comma, e.g. "link,image".</p> <p>Do not specify, if you have a lot of articles, images and/or media files (<= V4.6.15: wysiwyg/tinymce-lists).</p>	
--	--	---	--

Style editor, script editor and module templates editor related parameters

style_editor	wrap	{on, off} Default off. Defines the wrap attribute of the textarea to edit the CSS file. In case of 'on' the lines will be wrapped.	System, Clients, Users
script_editor	wrap	{on, off} Default off. Defines the wrap attribute of the textarea to edit the JS file.	System, Clients, Users
html_editor	wrap	{on, off} Default off. Defines the wrap attribute of the textarea to edit the HTML file.	System, Clients, Users

Eindeutige ID: #1143

Verfasser: Björn Behrens

Letzte Änderung: 2007-09-27 01:03